

VILLAGE OF TEUTOPOLIS DITCH TILING POLICY

1. Tile material must be concrete, corrugated steel or double wall PVC. PVC tiles, if used, shall have a minimum of one (1) foot of cover.
2. Minimum tile size shall be twelve (12) inches.
3. There must be enough cover over the pipe so as a swell or dip can be formed to allow storm water from road to drain in the culvert and not flow down the side of the roadway. If this cannot be done, the request shall be denied.
4. Catch basins shall be located at each property line and at any low spot. The catch basin must be a manufactured “tee” or constructed of block/brick, and must have a concrete floor so that no washing out or undermining can occur. The size of the catch basin shall be sufficient to the anticipated water shed, and shall be subject to Village approval.
5. The tiling of any ditch requires Village approval. In the event the Village deems it necessary to solicit the services, and or opinions, of their Engineer, the costs associated with the same shall be at the expense of the property owner.
6. The property owner wanting the ditch tiled will incur all expenses of tiling. This includes the tile piping, dirt, catch basins, equipment, labor, sand, engineering if necessary, etc.
7. Prior to the installation of the tile, the property owner shall notify the Village of their intentions, so that the Village may inspect the tile’s installation.
8. The Village, at the homeowner’s expense, will remove any unauthorized tiling of ditches.

I have read the above procedures on tiling of ditches and agree to abide by the policy set forth by the Village.

Name: _____ **Date:** _____

Approved by Village Foreman: _____ **Date:** _____